



USB-C to Gigabit Ethernet Adapter

With Power Delivery

Add lightning-fast multi-Gigabit wired connectivity to your desktop or laptop computer directly through your USB-C port

DUB-E135

- 1Gbps Ethernet Connectivity
- USB-C / Thunderbolt 3/4 Connector
- Auto Speed Detection
- Supports Crossover Detection
- Supports Full-Duplex Mode
- Two LED indicators
- Supports PD (Power Delivery) 100W
- Plug & Play
- Backwards compatible (10/100 Mbps)



Up to 1000 Mbps



1 Gigabit Ethernet
Connectivity



USB-C and Thunderbolt™
Support

| General | |
|----------------------------------|--|
| Device Interfaces | RJ-45 Ethernet Port (10/100/1000 Mbps), USB-C Connector |
| LED | Connection (green), Link/ACT (flashing orange) |
| Functionality | |
| IEEE Standard | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab |
| USB Specifications | USB 3.1 Gen 1, USB 3.0, USB 2.0 |
| Supports | IEEE 802.1P (Layer 2 Priority Encoding) IEEE 802.1Q (VLAN tagging) IEEE 802.3az (Energy Efficient Ethernet) IEEE 802.3ab (1GBASE-T) IEEE 802.3x (Full Duplex flow control) |
| Software | |
| Auto Speed Detection | 10/100/1000 Mbps |
| Crossover Detection | Auto-MDI/MDI-X |
| Power Management | Power Saving Mode when Ethernet cable is unplugged |
| Hot Pluggable | Yes |
| System Requirements | Windows XP/Vista/7/8/8.1/10/11, Mac OS/Nintendo Switch |
| Physical | |
| Operating Mode Power Consumption | 67 mA |
| Standby Mode Power Consumption | 55 mA |
| Cable Length | 180 mm |
| Dimensions | 80 x 25 x 15 mm |
| Weight | 33 g |
| Operating Temperature | 10 to 45 °C |
| Storage Temperature | 10 to 70 °C |
| Operating Humidity | 10% to 85% non-condensing |
| Storage Humidity | 5% to 90% non-condensing |
| Certifications | CE, RoHS |

