

Product Highlights

Full-Resolution Video

HDMI video up to 4K @ 30 Hz Ultra HD resolution for stunning videos and images with no lag

Ultra-Fast USB 3.0

SuperSpeed USB 3.0 technology up to 5Gbps enables you to transfer files up to 10 times faster than with USB 2.0, Support PD 100W fast charging

No Installation Needed

Plug and Play. Simply connect to an available USB Type-C or Thunderbolt 3/4 and enjoy HDMI video in seconds



DUB-M650

6-in-1 USB-C Hub with HDMI/Power Delivery

Features

HDMI Compatibility

- Ultra HD video resolution up to 4K @ 30Hz
- Supports HDMI 1.4 and DisplayPort Alternate Mode over USB-C
- HDCP 2.2 compatible

USB Type-C & Audio port with Simple Installation

- Two USB 3.0 SuperSpeed 5 Gbps ports
- One USB 3.0 Type-C port with data sync
- One USB 3.0 Type-C PD port with power delivery of up to 100W (20V/5A)
- One 3.5mm audio port
- Backwards compatible with USB 2.0 and USB 1.1 devices
- Simply plug it in and you're ready to go
- No additional hardware or software installation required

The DUB-M650 6-in-1 USB-C Hub with HDMI/Power Delivery allows you to instantly add a second display, two additional USB 3.0 ports, as well as one additional USB Type-C port to your ultraportable laptop or personal computer. Also DUB-M650 comes with an 3.5mm audio port for external headset. Just plug the DUB-M650 into an available USB Type-C port and you're ready to connect to your TV or monitor in full resolution with the reliability of a wired video connection. You can also connect up to 1 more USB devices, as well as sync one USB Type-C device, meaning that you don't have to give up that USB Type-C port this hub is connected to.

Hardware Overview



6-in-1 USB-C Hub with HDMI/Power Delivery

Technical Specifications

Connectivity

Device Interfaces	<ul style="list-style-type: none"> • Two USB 3.0 Type-A (female) ports • HDMI Port (3840 x 2160 or 4096 x 2160 pixels @ 60 Hz) backwards compatible to 1080p and 720p • One 3.5mm audio port 	<ul style="list-style-type: none"> • One USB 3.0 Type-C port with power delivery of up to 100 W (20 V @ 5 A) • USB Type-C Connector (Thunderbolt 3 / 4 compliant)
Standards	<ul style="list-style-type: none"> • HDM 1.4 • HDCP 2.2 	<ul style="list-style-type: none"> • DisplayPort Alternate Mode • USB Specification Version 3.0/2.0/1.1

General

Minimum System Requirements	<ul style="list-style-type: none"> • Computer running Microsoft Windows, Mac OS or Chrome OS 	<ul style="list-style-type: none"> • A USB Type-C Port with DisplayPort Alternate Mode support
Power Delivery	<ul style="list-style-type: none"> • USB Type-C port: 20 V @ 5 A 	

Physical

Dimensions (W x H x D)	<ul style="list-style-type: none"> • 131 x 32 x 11 mm 	<ul style="list-style-type: none"> • Cable length: 18cm
Weight	<ul style="list-style-type: none"> • 54.0 g 	
Power	<ul style="list-style-type: none"> • Input: Bus-powered 	<ul style="list-style-type: none"> • Consumption: 70 mA, 5 V DC
Temperature	<ul style="list-style-type: none"> • Operating: 0 to 70 °C (32 to 158 °F) 	<ul style="list-style-type: none"> • Storage: -25 to 85 °C (-13 to 185 °F)
Humidity	<ul style="list-style-type: none"> • Operating: 5% to 80% RH, non-condensing 	<ul style="list-style-type: none"> • Storage: 5% to 80% RH, non-condensing
Certifications	<ul style="list-style-type: none"> • CE • FCC 	<ul style="list-style-type: none"> • RoHS

For more information: www.dlink.com.sg

D-Link International.
Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved. E&OE.

Updated June 2024

D-Link®