# **D-Link**®

## **Product Highlights**

#### **Full-Resolution Video**

HDMI video up to 4K @ 60 Hz Ultra HD resolution or conventional VGA port for stunning videos and images with no lag

#### Ultra-Fast USB 3.0

SuperSpeed USB 3.0 technology up to 5Gbps enables you to transfer files up to 10 times faster than with USB 2.0, Support PD 100W fast charging

#### No Installation Needed

Plug and Play. Simply connect to an available USB Type-C or Thunderbolt 3/4 and enjoy HDMI video in seconds



### **DUB-M1150**

## 11-in-1 USB-C Docking station

#### **Features**

#### **HDMI Compatibility**

- Ultra HD video resolution up to 4K @ 60Hz
- Supports One HDMI 2.0 and DisplayPort Alternate Mode over USB-C
- HDCP 2.2 compatible

#### Plug and Play Simple Installation

- Three USB 3.0 SuperSpeed 5 Gbps ports
- One USB 3.0 Type-C port with data sync
- One USB 3.0 Type-C PD port with power delivery of up to 100W (20V/5A)
- One 3.5mm audio port
- One VGA port ( 1080P @ 60Hz)
- One SD Card Slot
- One Micro-SD (TF Flash) Slot
- One 1Gbps Ethernet Port
- Backwards compatible with USB 2.0 and USB 1.1 devices
- $\bullet\,$  Simply plug it in and you're ready to go
- No additional hardware or software installation required

The DUB-M1150 11-in-1 USB-C Docking Station with HDMI and Power Delivery enables you to effortlessly add a second display via HDMI or VGA to your ultraportable laptop or personal computer. It features three additional USB 3.0 ports, an extra USB Type-C port, a 3.5mm audio port for external headsets, and a high-speed 2.5Gbps Ethernet adapter. Simply plug the DUB-M1150 into an available USB Type-C port, and you can connect to your TV or monitor with a reliable, high-resolution wired video connection. The docking station also allows you to connect up to one more USB device and sync one USB Type-C device without sacrificing the USB Type-C port used for the hub. Additionally, it is equipped with both SD and Micro-SD card slots for external storage, making it an essential tool for enhancing work efficiency and streamlining device connectivity, suitable for both personal and professional use.

#### **Hardware Overview**





## 11-in-1 USB-C Hub with HDMI/Power Delivery

Technical Specifications		
Connectivity		
Device Interfaces	<ul> <li>Three USB 3.0 Type-A (female) ports</li> <li>HDMI Port (3840 x 2160 or 4096 x 2160 pixels @ 60 Hz) backwards compatible to 1080p and 720p</li> <li>One VGA (1080P @ 60Hz)</li> <li>One 3.5mm audio port</li> </ul>	<ul> <li>One USB 3.0 Type-C port with power delivery of up to 100 W (20 V @ 5 A)</li> <li>USB Type-C Connector (Thunderbolt 3 / 4 compliant)</li> <li>One SD Slot &amp; one Micro-SD slot</li> <li>One 1Gbps Ethernet port</li> </ul>
Standards	• HDMI 2.0 • HDCP 2.2 • DisplayPort Alternate Mode	USB Specification Version 3.0/2.0/1.1
General		
Minimum System Requirements	Computer running Microsoft Windows, Mac OS or Chrome OS	A USB Type-C Port with DisplayPort Alternate Mode support
Power Delivery	USB Type-C port: 20 V @ 5 A	
Physical		
Dimensions (W x H x D)	• 120 x 56x 16mm	Cable length: 18cm
Weight	• 90.0 g	
Power	Input: Bus-powered	Consumption: 8 6 mA, 5 V DC
Temperature	• Operating: 0 to 70 °C (32 to 158 °F)	• Storage: -25 to 85 °C (-13 to 185 °F)
Humidity	Operating: 5% to 80% RH, non-condensing	Storage: 5% to 80% RH, non-condensing
Certifications	• CE • FCC	• RoHS



### For more information: www.dlink.com.sg

