



APC Back-UPS 500, 230V without auto shutdown software, ASEAN

BR500CI-AS

Call for More Information (0) 2 617 5555

• Includes: (2) Detachable 1.8 m IEC power cords, User manual, Warranty card

Output	
Output power capacity	300 Watts / 500VA
Max Configurable Power (Watts)	300 Watts / 500VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz Sync to mains
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(3) IEC 60320 C13
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz Auto-sensing
Input Connections	IEC 60320 C14
Cord Length	1.8meters
Number of Power Cords	1

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	10hour(s)
Replacement Battery	APCRBC125 ☐
Expected Battery Life (years)	2 - 4

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.



Batteries & Runtime	
RBC Quantity	1
Battery Charge Power (Watts)	7 Watts
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Audible Alarm	Alarm when on battery: distinctive low battery alarm

Surge Protection and Filtering	
Surge energy rating	240Joules

Physical	
Maximum Height	185MM, 18.5CM
Maximum Width	115MM, 11.5CM
Maximum Depth	213MM, 21.3CM
Net Weight	4.9KG
Shipping weight	5.5KG
Shipping Height	257MM, 25.7CM
Shipping Width	190MM, 19.0CM
Shipping Depth	291MM, 29.1CM
Color	Black
Master Carton Units	1.0
Units per Pallet	60.0
SCC Codes	00731304269793

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 15240meters

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications



APC Back-UPS 500, 230V without auto shutdown software, ASEAN | BR500CI-AS | Downloaded on 03/11/2021 (EST)

Conformance	
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.