

APC EASY UPS BV 500VA, AVR, Universal Outlet, 230V

BV500I-MS

Call for More Information (0) 2 617 5555



- Includes: User manual

Output	
Output power capacity	300 Watts / 500VA
Max Configurable Power (Watts)	300 Watts / 500VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Unsynchronised
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(4) Universal receptacle
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz Auto-sensing
Input Connections	NEMA 5-15P
Cord Length	1.2meters
Input voltage range for main operations	170 - 280V
Number of Power Cords	1

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	8hour(s)
Expected Battery Life (years)	3 - 5
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Communications & Management

Control panel	LED Status display with on line : on battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	156Joules
---------------------	-----------

Physical

Maximum Height	93MM, 9.25CM
Maximum Width	161MM, 16.05CM
Maximum Depth	305MM, 30.5CM
Net Weight	3.9KG
Shipping weight	4.2KG
Shipping Height	237MM, 23.7CM
Shipping Width	143MM, 14.3CM
Shipping Depth	373MM, 37.3CM
Color	Black
SCC Codes	10731304338298

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 90 %
Operating Elevation	0 - 2032.1meters
Storage Temperature	-20 - 50 °C
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	40.0dBA
Protection Class	IP20

Conformance

Approvals	CE
Standard warranty	2 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC EASY UPS BV 500VA, AVR, Universal Outlet, 230V | BV500I-MS | Downloaded on 03/11/2021 (EST)



Sustainable Offer Status

RoHS	Compliant
------	-----------

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.