

True Online Double Conversion UPS

HT11 series High Frequency Online UPS

1-3KVA 1Phase:1Phase

Specification:

Model	HT1101S	HT1101L	HT1102S	HT1102L	HT1103S	HT1103L
Capacity	1kVA/900W		2kVA/1800W		3kVA/2700W	
Input						
Voltage	220/230/240Vac					
Voltage Range	220Vac \pm 25%					
Frequency	50/60Hz \pm 10%					
Output						
Voltage	220VAC \pm 5%					
Frequency	50/60Hz \pm 1%					
Harmonic Distortion	\leq 3% (linear load); \leq 5% (non-linear load)					
Waveform	Pure Sine Wave					
Power Factor	0.9					
Crest Factor	3:1					
Efficiency						
AC to AC	$>$ 85%					
Battery Mode	$>$ 83%					
Battery						
Battery Voltage	36Vdc		72Vdc		96Vdc	
Battery Number	12V9.6AH*3pcs	External	12V9.6AH*6pcs	External	12V9.6AH*8pcs	External
Backup Time (Full Load)	5 Mins	Depend On Load	5 Mins	Depend On Load	5 Mins	Depend On Load
Communication						
Interface	RS232 / SNMP card(Optional) / USB(Optional)					
Environment						
Operation Temperature	0~40°C					
Humidity	0~95% (non-condensing)					
Audible Noise	\leq 45dB	\leq 50dB				
Physics						
Dimensions(W*D*H)mm	144*350*236		190*425*336		190*425*33	
Weight (KG)	12	6	22	10	26	10