





APC Replacement Battery Cartridge #43

RBC43

Call for More Information (0) 2 617 5555

 Includes: All required connectors, Battery recycling guide, Installation guide, Metallic battery tray or enclosure, Reusable packaging

Output	
Battery Output Voltage	48 V
Input	
Number of Power Cords	1
Batteries & Runtime	
Battery type	Lead-acid battery
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Physical	
· · · · · · · ·	
Maximum Height	76MM, 7.6CM
-	76MM, 7.6CM 216MM, 21.6CM
Maximum Height	
Maximum Height Maximum Width	216MM, 21.6CM
Maximum Height Maximum Width Maximum Depth	216MM, 21.6CM 533MM, 53.3CM
Maximum Height Maximum Width Maximum Depth Net Weight	216MM, 21.6CM 533MM, 53.3CM 19.09KG
Maximum Height Maximum Width Maximum Depth Net Weight Shipping weight	216MM, 21.6CM 533MM, 53.3CM 19.09KG 20.45KG
Maximum Height Maximum Width Maximum Depth Net Weight Shipping weight Shipping Height	216MM, 21.6CM 533MM, 53.3CM 19.09KG 20.45KG 229MM, 22.9CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Replacement Battery Cartridge #43 | RBC43 | Downloaded on 03/16/2021 (EST)



Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters
Conformance	
Standard warranty	1 year repair or replace, 30 days (Japan only)
Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Proposition 65 Warning	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.