

## Technical Specifications

APC Smart-UPS SRT 6000VA 230V | SRT6KXLI | Downloaded on 03/15/2021 (EST)



## APC Smart-UPS SRT 6000VA 230V SRT6KXLI

Call for More Information (0) 2 617 5555

- Includes: CD with software, Documentation CD, Installation guide, Removable support feet, Temperature probe, USB cable, Warranty card, Web/SNMP management card

Output	
Output power capacity	6.0kWatts / 6.0kVA
Max Configurable Power (Watts)	6.0kWatts / 6.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(6) IEC 60320 C13 (6) IEC 320 C13 (1) Hard Wire 3-wire (H N + G) (2) IEC Jumpers (4) IEC 320 C19 (4) IEC 60320 C19
Bypass	Internal bypass (automatic and manual)


Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz Auto-sensing
Input Connections	Hard wire 3-wire (1P + N + E)
Input voltage range for main operations	100 - 275 Adjustable (half load), 160 - 275V
Other Input Voltages	220, 240

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS SRT 6000VA 230V | SRT6KXLI | Downloaded on 03/15/2021 (EST)

### Batteries & Runtime

Battery type	Lead-acid battery
Typical recharge time	1.5hour(s)
Nominal Battery Voltage	192 V
Replacement Battery	<a href="#">APCRBC140</a> 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Charge Power (Watts)	597 Watts
Extendable Run Time	1
Extended Run Options	APC-Smart-UPS-SRT-6000VA-230V (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

### Communications & Management

Interface Port(s)	RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

### Surge Protection and Filtering

Surge energy rating	480Joules
---------------------	-----------

### Physical

Maximum Height	432MM, 43.2CM
Maximum Width	174MM, 17.4CM
Maximum Depth	719MM, 71.94CM
Net Weight	60.0KG
Shipping weight	67.0KG
Shipping Height	370MM, 37.0CM
Shipping Width	610MM, 61.0CM

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC Smart-UPS SRT 6000VA 230V | SRT6KXLI | Downloaded on 03/15/2021 (EST)

### Physical

Shipping Depth	960MM, 96.0CM
Color	Black
Units per Pallet	6.0

### Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3048meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	1300.0BTU/hr
Protection Class	IP20

### Conformance

Approvals	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

### Sustainable Offer Status

RoHS	Compliant
------	-----------

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.