



APC Easy UPS On-Line SRV Ext. Runtime 1000VA 230V with External Battery Pack

SRV1KIL

Call for More Information (0) 2 617 5555

- Includes: (1) DC cable, Basic UPS signalling RS-232 cable, CD with software, Country-specific detachable power cord, USB cable, User manual

Output	
Output power capacity	800 Watts / 1.0kVA
Max Configurable Power (Watts)	800 Watts / 1.0kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Efficiency at Full Load	88.0 %
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz Sync to mains
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double conversion online
Waveform type	Sine wave
Output Connections	(3) IEC 60320 C13
Bypass	Internal bypass (automatic and manual)

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC 60320 C14
Cord Length	1.5meters
Input voltage range for main operations	110 - 285 Adjustable (half load), 160 - 280V
Number of Power Cords	1
Efficiency at Full Load	88.0 %

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Input	
Other Input Voltages	220, 240

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	4hour(s)
Extended Run Options	APC-Easy-UPS-On-Line-SRV-Ext-Runtime-1000VA-230V-with-External-Battery-Pack (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	DB-9 RS-232, USB
Control panel	Multifunction LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering	
Surge energy rating	600Joules

Physical	
Maximum Height	238MM, 23.8CM
Maximum Width	290MM, 29.0CM
Maximum Depth	400MM, 40.0CM
Net Weight	24.0KG
Shipping weight	26.7KG
Shipping Height	355MM, 35.5CM
Shipping Width	470MM, 47.0CM
Shipping Depth	525MM, 52.5CM
Color	Black

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 3048meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15240meters
Audible noise at 1 meter from surface of unit	50.0dBA
Protection Class	IP20

Conformance	
Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.