

DS-7608NI-K1/8P



8-ch 1U 8 PoE 4K NVR

- Up to 8-ch IP camera inputs
- H.265+/H.265/H.264+/H.264 video formats
- Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity
- Up to 80 Mbps incoming bandwidth



☆ Add to Favorites

Specification

- **Video And Audio**
- **IP Video Input**8-ch
- **HDMI Output**1-ch, 4K (4096x2160) /30Hz, 4K (3840x2160) /30Hz, 2K (2560x1440) /60Hz, 1920x1080/60Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz; HDMI/VGA simultaneous output,
- **VGA Output**1-ch, 1920*1080/60Hz, 1280*1024/60Hz, 1280*720/60Hz,HDMI/VGA simultaneous output,
- **Incoming Bandwidth**80 Mbps
- **Outgoing Bandwidth**80 Mbps
- **Audio Output**1-ch, RCA (Linear, 1 KΩ)
- **Two-Way Audio**1-ch, RCA (2.0 Vp-p, 1 k Ω)

- **Decoding**
- **Decoding Format**H.265/H.265+/H.264/H.264+/MPEG4
- **Decoding Capability**5 x1080P
- **Synchronous Playback**8-ch
- **Recording Resolution**8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA
/720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
- **Network**
- **Network Protocol**TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP,
SMTP, NFS, iSCSI, UPnP™, HTTPS
- **Network Interface**1, RJ-45 10/100 Mbps self-adaptive Ethernet
interface
- **PoE**
- **Interface**8, RJ-45 10/100 Mbps self-adaptive Ethernet interface
- **Power**≤ 75W
- **RAID**
- **RAID Type**No

- **Auxiliary Interface**
 - **SATA1** SATA interface
 - **Capacity** Up to 8TB capacity for each disk
 - **USB Interface** 2 × USB 2.0
 - **Alarm In/Out** N/A (4/1 is optional)
 - **General**
 - **Power Supply** 48 VDC, 1.88 A
 - **Consumption** ≤ 10 W (without enabling PoE)
 - **Working Temperature** -10 to +55° C (+14 to +131° F)
 - **Working Humidity** 10 to 90 %
 - **Chassis** 1U chassis
 - **Dimension (W × D × H)** 320 × 240 × 48 mm (12.4" × 9.4" × 1.9")
 - ≤ 1 kg (2.2 lb)
-