

# Product datasheet

Specifications



## APC Smart-UPS, Line Interactive, 1000VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartSlot, AVR, LCD

SMT1000RMI2U

### Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead time** Usually in Stock

### Main

**Main Input Voltage** 230 V

**Other Input Voltage** 220 V  
240 V

**Main Output Voltage** 230 V

**Other Output Voltage** 220 V  
240 V

**Rated power in W** 700 W

**Rated power in VA** 1000 VA

**Input Connection Type** IEC 320 C14

**Output connection type** 4 IEC 320 C13  
2 IEC Jumpers

**Number of rack unit** 2U

**Number of cables** 1

**Battery type** Lead-acid battery

**Provided equipment** USB cable  
Documentation CD  
Installation guide  
Rack mounting support rails  
Smart UPS signalling RS-232 cable

### Batteries & Runtime

**Additional information** Configurable for 220 : 230 or 240 nominal output voltage

**Extended runtime** 0


**Number of battery filled slots** 0

**Number of battery free slots** 0

**Battery recharge time** 3 h

**Number of battery replacement quantity** 1

**Battery life** 4...6 year(s)

Replacement battery	<a href="#">APCRBC157</a> 
Battery power in VAH	336 VAh runtime
Battery charger power	112 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black
Height	8.5 cm
Width	48 cm
Depth	47.5 cm
Net weight	28.18 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	700 W
Transfer time	2 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

## Conformance

Product certifications	CSA EAC RCM VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Acoustic level	45 dBA
Heat dissipation	56 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Optional
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.1 cm
Package 1 Width	59.4 cm
Package 1 Length	60.3 cm
Package 1 Weight	31.45 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	16
Package 2 Height	135 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	502.224 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

### Contractual warranty

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

### Recommended replacement(s)