

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 750VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartSlot, AVR, LCD

SMT750RMI2U

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually in Stock

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 500 W

Rated power in VA 750 VA

Input Connection Type IEC 320 C14

Output connection type 4 IEC 320 C13
2 IEC Jumpers

Number of rack unit 2U

Number of cables 1

Battery type Lead-acid battery

Provided equipment USB cable
Documentation CD
Installation guide
Rack mounting support rails
Smart UPS signalling RS-232 cable

Batteries & Runtime

Additional information Configurable for 220 : 230 or 240 nominal output voltage

Extended runtime 0


Number of battery filled slots 0

Number of battery free slots 0

Battery recharge time 3 h

Number of battery replacement quantity 1

Battery life 4...6 year(s)

Replacement battery	APCRBC123 
Battery power in VAH	168 VAh runtime
Battery charger power	56 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	40.6 cm
Net weight	17.27 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	750 VA
Maximum configurable power in W	500 W
Transfer time	2 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

Conformance

Product certifications	CE CSA EAC RCM TÜV VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	42 dBA
Heat dissipation	46 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Optional
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	54.6 cm
Package 1 Length	58.4 cm
Package 1 Weight	21.23 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	10
Package 2 Height	137 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	225 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

Recommended replacement(s)